

	ProZone ProR312J	Honeywell HZ311	ZoneFirst MMP3	The ProZone Difference
Zones on Panel	3	3	3	<ul style="list-style-type: none"> <li>Compatible with Gas/Electric, Conventional Heat Pump and Dual Fuel Heat Pump equipment. Competition requires more expensive panel for heat pump equipment.</li> <li>Out of the box operation - Use the jumper plugs to select equipment and panel is ready to go.</li> <li>One stage of heating and two stages of cooling. Competition requires more expensive panel for two stage cooling.</li> <li>Plug and play dampers eliminate the time and errors associated with traditional wiring. Not offered by Honeywell.</li> <li>Plug-in display module is provided free to contractors and can be used to walk the installer through installation, test the installation, save panel configurations for cloning multiple panels and set advanced options. Competition requires more expensive panel and does not offer cloning option.</li> <li>Adjustable heating / cooling discharge air temperature limits set using the PDMi3. Not offered by competition.</li> <li>Built-in fresh air controller meeting ASHRAE 62-2. Includes fresh air damper connector on panel. Competition requires purchasing external fresh air controller.</li> <li>All LED indicators are visible with panel cover on. Competition requires the panel cover to be removed to view some indicators.</li> </ul>
Expandable	No.	No.	No.	
Compatible Equipment				
Gas/Electric	Yes.	Yes.	Yes.	
Conventional Heat Pump	Yes.	No.	No.	
Dual Fuel Heat Pump	Yes.	No.	No.	
Equipment Selection	Jumper plugs.	Only G/E.	Only G/E.	
Heating Stages	One.	One.	One.	
Cooling Stages	Two.	One.	One.	
Damper Wiring	Plug and Play	Wired	Plug and Play	
Damper Construction	Damper uses foam gasket between dual blades with efficient airflow.	Uses 1/2-inch foam gasket attached to sleeve. Reduces effective damper diameter by 1 inch.	Uses 1/2-inch foam gasket attached to sleeve. Reduces effective damper diameter by 1 inch.	
Damper Actuator Type	Power Open/Close.	Spring Return.	Power Open/Close.	
Damper Actuator VA	2.4VA Operating .7VA Holding	7VA	2.4VA Operating .7VA Holding	
Plug-in Display for changing options, monitoring installation and cloning.	Yes, using the PDMi3 provided at no cost to installers.	No.	No.	
Adjustable heating / cooling discharge air temperature limits.	Yes, using the PDMi3 provided at no cost to installers.	No.	No.	
Built-in fresh air controller to meet ASHRAE 62-2 and Title24.	Yes. Includes a connector for the fresh air damper.	No. Requires an external fresh air controller.	No. Requires an external fresh air controller.	
Fresh Air Damper Connector.	Yes.	No.	No.	
Zone1 Thermostats.	Heat/Cool or Heat Pump.	Heat/Cool.	Heat/Cool.	
Zone2 and 3 Thermostats.	Heat/Cool.	Heat/Cool.	Heat/Cool.	
LED Indicators				
Zone Thermostat Call Status	Yes.	No.	No.	
Equipment Call Status	Yes.	Yes.	Yes.	
Zoning Panel Status	Yes.	Yes.	Yes.	
Damper Position	Yes.	Yes.	Yes.	